



# MATERIAL SAFETY DATA SHEET

Page 1 of 5

## SIKALASTOMER 65

### HMIS

HEALTH 0

FLAMMABILITY 1

REACTIVITY 0

PERSONAL PROTECTION

### 1. Product And Company Identification

#### Supplier

Sika Corporation  
201 Polito Ave  
Lyndhurst, NJ 07071

Company Contact: EHS Department  
Telephone Number: 201-933-8800  
FAX Number: 201-933-9379  
Web Site: www.sikausa.com

#### Manufacturer

None Given

#### Supplier Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300  
INTERNATIONAL: 703-527-3887

#### Manufacturer Emergency Contacts & Phone Number

None Given

Issue Date: 08/05/2003

Product Name: SIKALASTOMER 65  
Chemical Family: BUTYL SEALANT  
Chemical Formula: COMPLEX MIXTURE  
MSDS Number: 2807

### 2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
CALCIUM CARBONATE	1317-65-3	
CARBON BLACK	1333-86-4	
HYDRATED AMORPHOUS SILICA	63231-67-4	
TALC	14807-96-6	
TITANIUM DIOXIDE	13463-67-7	

### 3. Hazards Identification

#### Eye Hazards

EYE CONTACT UNLIKELY IN NORMAL USE BUT ACTS AS A MECHANICAL IRRITANT.

#### Skin Hazards

HAS NO TOXIC OR INFLAMMATORY EFFECT ON SKIN. HAS NO SENSITIZING EFFECT.

#### Ingestion Hazards

NOT NORMALLY INGESTED IN INDUSTRIAL USE. INGESTION MAY CAUSE SLIGHT GASTRO-INTESTINAL DISCOMFORT.

## SIKALASTOMER 65

### 3. Hazards Identification - Continued

#### Inhalation Hazards

NO INHALATION EFFECTS ARE KNOWN OR REPORTED.

### 4. First Aid Measures

#### Eye

RINSE EYES THOROUGHLY WITH WATER FOR AT LEAST 15 MINUTES. CONSULT PHYSICIAN.

#### Skin

NONE REQUIRED. IN ACCORDANCE WITH GOOD HYGIENIC PRACTICE, WASH WITH SOAP AND WATER AFTER USE.

#### Ingestion

IF INGESTED, DO NOT INDUCE VOMITING. IF DISCOMFORT PERSISTS, CALL A PHYSICIAN.

#### Inhalation

REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED, INSTITUTE ARTIFICIAL RESPIRATION. CONSULT WITH PHYSICIAN.

### 5. Fire Fighting Measures

**Flash Point:** 400 °F 204 °C

**Flash Point Method:** PMCC

**Autoignition Point:** UNKNOWN °F

**Flammability Class:** NCMB

**Lower Explosive Limit:** N/AP

**Upper Explosive Limit:** N/AP

#### Fire And Explosion Hazards

NONE KNOWN

#### Extinguishing Media

CARBON DIOXIDE, WATER, DRY CHEMICAL, FOAM, AS FOR SURROUNDING FIRES.

#### Fire Fighting Instructions

WEAR NIOSH/MSHA APPROVED SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR, AS FOR SURROUNDING FIRES.

### 6. Accidental Release Measures

PICK OR SCRAPE UP MATERIAL AND PLACE IN SUITABLE CONTAINER FOR DISPOSAL.  
CLEAN AREA WITH A NON-FLAMMABLE SOLVENT.

### 7. Handling And Storage

#### Handling And Storage Precautions

STORE IN COOL DRY PLACE. KEEP OUT OF REACH OF CHILDREN. FOR INDUSTRIAL USE ONLY.

### 8. Exposure Controls/Personal Protection

#### Engineering Controls

NO SPECIAL VENTILATION REQUIRED.

#### Eye/Face Protection

NONE REQUIRED.

#### Skin Protection

NONE REQUIRED.

#### Respiratory Protection

NONE REQUIRED.

## SIKALASTOMER 65

### 8. Exposure Controls/Personal Protection - Continued

#### Other/General Protection

AS REQUIRED BY YOUR COMPANY.

#### Ingredient(s) - Exposure Limits

CALCIUM CARBONATE

ACGIH TLV-TWA: 10 mg/m<sup>3</sup>

OSHA TRANS. PEL-TWA: 5 MG/M<sup>3</sup>

NTP N/AP

IARC N/AP

CARBON BLACK

ACGIH TLV-TWA: 3.5 mg/m<sup>3</sup>

OSHA PEL-TWA: 3.5 mg/m<sup>3</sup>

NTP N/AP

IARC N/AP

HYDRATED AMORPHOUS SILICA

OSHA TWA: 15MCM

ACGIH N/E

NTP N/AP

IARC N/AP

TALC

ACGIH TLV-TWA: 2 mg/m<sup>3</sup>

OSHA PEL-TWA: 20 mppcf

NTP N/AP

IARC N/AP

TITANIUM DIOXIDE

ACGIH TLV-TWA: 10 mg/m<sup>3</sup>

OSHA PEL-TWA: 15 mg/m<sup>3</sup>

NTP N/AP

IARC N/AP

### 9. Physical And Chemical Properties

#### Appearance

WHITE, GRAY OR BLACK TACKY SOLID

#### Odor

NO ODOR

**Chemical Type:** Pure

**Melting Point:** N/AP °F

**Boiling Point:** N/AP °F

**Specific Gravity:** 1.35

**Molecular Weight:** 0.00

**Vapor Pressure:** N/AP

**Vapor Density:** N/AP

**Solubility:** INSOLUBLE

**Evaporation Rate:** N/AP

VOC = 0.08 lbs/gal

### 10. Stability And Reactivity

**Stability:** STABLE

**Hazardous Polymerization:** WILL NOT OCCUR

#### Conditions To Avoid (Stability)

NONE KNOWN

# MATERIAL SAFETY DATA SHEET

Page 4 of 5

## SIKALASTOMER 65

### 10. Stability And Reactivity - Continued

#### Incompatible Materials

STRONG OXIDIZERS

#### Hazardous Decomposition Products

CARBON MONOXIDE, CARBON DIOXIDE AND HYDROCARBONS UPON COMBUSTION.

#### Conditions To Avoid (Polymerization)

NONE KNOWN

### 11. Toxicological Information

#### Miscellaneous Toxicological Information

NONE KNOWN

#### Conditions Aggravated By Exposure

NONE KNOWN

### 12. Ecological Information

No Data Available...

### 13. Disposal Considerations

DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL ENVIRONMENTAL REGULATIONS.

### 14. Transport Information

#### Proper Shipping Name

SIKALASTOMER 65

#### Hazard Class

NOT DOT REGULATED

### 15. Regulatory Information

No Data Available...

### 16. Other Information

#### HMIS Rating

Health: 0

Fire: 1

Reactivity: 0

#### Precautionary Label

CALCIUM CARBONATE 1317-65-3, CARBON BLACK 1333-86-9  
, SILICA 63231-67-4, TALC 14807-96-6, TITANIUM DIOX  
IDE 13463-62-7

#### Revision/Preparer Information

MSDS Preparer: EHS Departmnet

MSDS Preparer Phone Number: 201-933-8800

This MSDS Supercedes A Previous MSDS Dated: 04/23/1998

### Disclaimer

The data in this Material Safety Data Sheet relates only to the specific material herein and does not relate to use in combination with any other material or in any process. The information set forth herein is based on technical data that Sika believes to be reliable as of the date hereof. Since conditions of use are outside our control, we make no warranties, express or implied and assume no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under or a recommendation to infringe on any patents.

# MATERIAL SAFETY DATA SHEET

## SIKALASTOMER 65

**Disclaimer - Continued**

SIKA CORPORATION